

# Mono-Coat® 1907RAS

## Anti-Static Agent

Mono-Coat® 1907RAS is a water-based anti-static agent developed to eliminate the static that is generated during the rotational molding process. This product was formulated to be applied directly on the tool and is compatible with all grades of polyethylene resins.

### Typical Properties

Appearance	Off-white fluid
Density, lbs/gal; kg/l	8/50; 1.02
Storage Stability, unopened container	6 months

### Application

Wipe on molded surface after application of release agent. Application is required after every cycle.

### Storage

Do not store at temperatures above 100°F/38°C. Keep from freezing. Keep container tightly sealed to prevent evaporation and/or moisture contamination.

### Handling

We believe Mono-Coat® 1907RAS has a low degree of hazard when used as intended. For more information, request a copy of Chem-Trend's Material Safety Data Sheet.

### Packaging

Mono-Coat® 1907RAS is available in 1-gallon (3.8-liter), 5-gallon (20-liter) and 55-gallon (208-liter) containers.

While the technical information and suggestions for use contained herein are believed to be accurate and reliable, nothing stated in this bulletin is to be taken as a warranty either expressed or implied.

### Further Information

Request information on our complete range of materials: custom-formulated release agents for polyurethane molding; tire lubes and bladder coatings; Mono-Coat® semi-permanent release coatings; aerosol formulations; mold cleaners and sealers; specialized coatings and application equipment.